



Order form

for the planning of special switching programs for KK type rotary switches

Type

- ☐ KK0-20-...
☐ KK1-32-...
☐ KK2-40-...
☐ KK2-63-...
☐ KK2-80-...
☐ KK2-115-...
☐ KK3-115-...
☐ KK4-150-...
☐ KK5-315-...

Version

- ☐ Normal
☐ Plastic enclosure

☐ Lockable
☐ Padlockable
☐ Switch-disconnector
☐ Emergency-stop switch

☐ Rotating
☐ Returning control

☐ Door coupling

Switching angel


- ☐ 30°
☐ 45°
☐ 60°
☐ 90°

Mounting


- ☐ front
☐ rear
☐ front with 2pcs screws
☐ front and rear

Front plate

30°/60°



45°/90°



Contact-chamber No	Terminal position	Contact position: open: ☐ closed: ☒ returning control: ☐												Links	Terminal indication	Links
		Handle positions: 30° 45° 60° 90°														
		1	2	3	4	5	6	7	8	9	10	11	12			
1															☐ 1 — ☐ 2 ☐	
															☐ 3 — ☐ 4 ☐	
2															☐ 5 — ☐ 6 ☐	
															☐ 7 — ☐ 8 ☐	
3															☐ 9 — ☐ 10 ☐	
															☐ 11 — ☐ 12 ☐	
4															☐ 13 — ☐ 14 ☐	
															☐ 15 — ☐ 16 ☐	
5															☐ 17 — ☐ 18 ☐	
															☐ 19 — ☐ 20 ☐	
6															☐ 21 — ☐ 22 ☐	
															☐ 23 — ☐ 24 ☐	
7															☐ 25 — ☐ 26 ☐	
															☐ 27 — ☐ 28 ☐	
8															☐ 29 — ☐ 30 ☐	
															☐ 31 — ☐ 32 ☐	
9															☐ 33 — ☐ 34 ☐	
															☐ 35 — ☐ 36 ☐	
10															☐ 37 — ☐ 38 ☐	
															☐ 39 — ☐ 40 ☐	
11															☐ 41 — ☐ 42 ☐	
															☐ 43 — ☐ 44 ☐	
12															☐ 45 — ☐ 46 ☐	
															☐ 47 — ☐ 48 ☐	